Technical Data Sheet

B773 – Aluminium Anti-seize Revised 03.08.10



B773 Aluminium Anti-Seize

PRODUCT DESCRIPTION

B773 is an effective pre-assembly compound and thread lubricant. Which can be used where the exclusion of copper is required, for example where copper can be electrically or chemically active. It is particularly recommended for use with chemicals that can react with copper, such as ammonia in refrigerators, is likely to be experienced.

APPLICATIONS

B773 is recommended for use with chemicals that can react with copper. B773 can be used on threaded part, reduces torque, prevents seizing and galling.

INSTRUCTIONS FOR USE

Clean mating surfaces for application. Note when grinding or wire brushing use a dust mask. Dust from cleaning threads may contain metal compounds. Inhalation may cause lung injury or other harm. Apply a thin coating to threads, flats, nuts and bolts. Assemble and wipe away any excess.

HEALTH & SAFETY IN USE

This technical information sheet for does not constitute a Material Safety Data Sheet (MSDS). Before using this product ensure you have read and fully understand the MSDS.

TECHNICAL FEATURES

| Colour | Silver |
|---------------------|-----------------------|
| Base | Bentone (infusible) |
| Solubility | Insoluble in water |
| Temperature range | Any sub-zero - 1100°C |
| Flash point of base | 250°C |
| oil | |

PRESENTATION

| Tin | 500g |
|-----|------|
|-----|------|